

<b>Sport Flooring 4.5 / 6.5 /8.0</b>					
	<b>Standard</b>	<b>Unit</b>	<b>4.5MM</b>	<b>6.5MM</b>	<b>8.0MM</b>
<b>Description</b>					
<b>Roll Length</b>	EN 426	m	20/15	20/15	20/15
<b>Roll Width</b>	EN 426	m	1.8	1.8	1.8
<b>Total Thickness</b>	EN 428	mm	4.5	6.5	8
<b>Thickness Of Wearlayer</b>	EN 428	mm	0.6	0.8	0.8
<b>Weight</b>	EN 430	kg/m2	3.3-3.5	4.5-4.7	5.5-5.7
<b>Technical Characteristics</b>					
<b>Indentation Resistance</b>	EN 1516	mm	≤0.5	≤0.6	≤0.6
<b>Abrasion Resistance</b>	EN 5470-1	mg	≤300	≤300	≤300
<b>Impact Resistance</b>	DIN 18032	N/m	≥8	≥8	≥8
<b>Sports Characteristics</b>					
<b>Shock Absorption</b>	DIN 18032	%	≥20	≥24	≥28
<b>Friction Coefficient</b>	DIN 18032	—	0.45	0.55	0.6
<b>Ball Bounce</b>	DIN 18032	%	≥98	≥98	≥98
<b>Classification</b>					
<b>Fire Rating</b>	CE			Cfl - S1	
<b>Surface Treatment</b>	—	—		E-Clean	
<b>Antibacterial and fungicidal Treatment</b>	—	—		E-Safe	